



0928^{*)}, 0928-P^{*)}

Access Control

Active Cotag clamshell card

The **0928/0928-P** is an active card that includes a lithium battery which enables it to provide hands-free functionality when it is used together with Cotag hands-free readers. For example, the combination of the 0928/0928-P card and the HF500-Cotag reader results in a reading range of approximately 102 cm. The reading range when the 0928/0928-P is used in combination with Cotag proximity readers varies from approximately 12 to 32 cm. 0928/0928-P cards are particularly useful in environments where some cardholders are disabled or often have their hands full (i.e. a hospital or warehouse).

One of the major advantages of Cotag technology is that active and passive cards can be mixed in the same system to provide ultimate convenience and cost-efficiency.

^{*)} The **0928** is a tag without any numbers encoded. Customer needs to program the complete number segment.

The **0928-P** is a 0928 tag which is encoded according to customer specification.

Technical data

0928, 0928-P

Dimensions (W x H x D) 53.89 x 85.85 x 2.89 mm

Card read distance

Reader	HF500	BC5511	5516	HD500	PR500	PP500	SP500	PM500
Card								
0928	Up to 102 cm	Up to 89 cm	Up to 300 cm	Up to 26 cm	Up to 32 cm	Up to 12 cm	Up to 29 cm	Up to 23 cm

Details for ordering

Type	Part no	Designation
0928	GBI:51-501	Active non-encoded Cotag clamshell card
0928-P	GBI:51-505	Active customized encoded Cotag clamshell card. Minimum order quantity: 100 pcs

Issued by
Siemens AB
Security Products
International Headquarters
Englundavägen 7
SE-171 24 Solna
Tel. +46 8 629 0300

© 2011 Copyright by Siemens AB

Data and design subject to change without notice.
Supply subject to availability.

www.siemens.com/securityproducts

Document no. **A6V10330058**

Edition 05.2010