


Steel Door Contacts

1078/1076 Series



OVERVIEW

The Interlogix 1078 Series Steel Door contacts are designed specifically for use in the steel doors commonly found in commercial building applications. The unique housing design features a rugged unibody construction with flexible ribbed sides for quick, secure installation without gluing. The magnet housing isolates the magnet from the surrounding steel for maximum gap distances, both make and break. Over seven models including: Wide Gap, SPDT, DPDT, and Biased for High Security applications make the 1078 Series the most widely used and comprehensive line available.

On available models a terminal connection (T) makes installation easier. Simply strip the wire, insert it into the terminal block and tighten. The terminal accepts any wire size from 14 to 22 gauge, and has a unique one piece design for added strength.

An optional Rare Earth Magnet is available. It is designed for use in metal entry/exit doors with a channel in the top of the door. The magnet eliminates the need to cut a mounting hole in the door channel. The flexible magnet housing can be compressed to accommodate a variety of channel widths for quick, easy installation. Adhesive is recommended.

The contact contains a hermetically sealed magnetic reed switch. The reed shall be potted in the contact housing with a polyurethane based compound. Contact and magnet housing shall snap-lock into a 3/4" or 1" dia. hole. Housings shall be molded of flame retardant ABS plastic. Color of housings shall be off-white, gray or mahogany brown. The magnet shall be made of Alnico V. Rare Earth Magnet shall be made of neodymium iron boron.

Snap-lock insulation bushing for tight fit and maximum gap in steel. Both contact and magnet plastic housings are constructed of one piece of thick-walled ABS plastic for maximum strength and durability.

STANDARD FEATURES

- Fly leads and terminal options available
- Designed specifically for use in steel doors
- Special ribbed sides allow for easy installation
- Rugged unibody construction for maximum durability and reliability
- Terminal models available for easier installation
- Regular, Wide Gap, SPDT, DPDT, and High Security models available
- Rare Earth Magnet designed for steel door with top channel available

Steel Door Contacts

1078/1076 Series

North America
T 855-286-8889

Latin America
T 561-998-6114

Ordering Information

| | |
|--------------------|--|
| 1076CH-N | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Higher Security, Biased for Higher Security Applications, Single Pole-Double Throw, White |
| 1076C-M | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, SPDT, 3/8" Gap Size, Single Pole-Double Throw, Brown |
| 1076C-N | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, SPDT, 3/8" Gap Size, Single Pole-Double Throw, White |
| 1076CW-M | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Wide Gap, SPDT, 3/4" Gap Size, Single Pole-Double Throw, Brown |
| 1076CW-N | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Wide Gap, SPDT, 3/4" Gap Size, Single Pole-Double Throw, White |
| 1076D-G | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, DPDT, 1/2" Gap Size, Double Pole-Double Throw, Gray |
| 1076D-M | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, DPDT, 1/2" Gap Size, Double Pole-Double Throw, Brown |
| 1076D-N | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, DPDT, 1/2" Gap Size, Double Pole-Double Throw, White |
| 1076-G | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, SPDT, 1/2" Gap Size, Single Pole-Double Throw, Gray |
| 1076H-N | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, High Security, SPDT, Biased for Higher Security, 1/2" Gap, Single Pole-Double Throw, White |
| 1076-M | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, SPDT, 1/2" Gap Size, Single Pole-Double Throw, Brown |
| 1076-N | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, SPDT, 1/2" Gap Size, Single Pole-Double Throw, White |
| 1076W-M | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, SPDT, Wide Gap, 1" Gap Size, Single Pole-Double Throw, Brown |
| 1076W-N | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, SPDT, Wide Gap, 1" Gap Size, Single Pole-Double Throw, White |
| 1078C1-M | 1078C w/1929 Magnet, Brown |
| 1078C-G | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Closed Loop, 3/8" Gap Size, Gray |
| 1078C-M | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Closed Loop, 3/8" Gap Size, Brown |
| 1078C-N | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Closed Loop, 3/8" Gap Size, White |
| 1078CT-M | Recessed Steel Door Terminal Contact, 3/4" Diameter, 7/8" Gap Size (3/8" in Steel), Brown |
| 1078CT-N | Recessed Steel Door Terminal Contact, 3/4" Diameter, 7/8" Gap Size (3/8" in Steel), White |
| 1078CTW-N | Recessed Steel Door Terminal Contact, 3/4" Diameter, Wide Gap, 2" Gap Size (3/4" in Steel), White |
| 1078CW-G | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Closed Loop, Wide Gap, 3/4" Gap Size, Gray |
| 1078CW-M | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Closed Loop, Wide Gap, 3/4" Gap Size, Brown |
| 1078CW-N | Recessed Steel Door Contact w/Wire Leads, 3/4" Diameter, Closed Loop, Wide Gap, 3/4" Gap Size, White |
| 1078-G | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, 1/2" Gap Size, Closed Loop, Gray |
| 1078-M | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, 1/2" Gap Size, Closed Loop, Brown |
| 1078-N | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, 1/2" Gap Size, Closed Loop, White |
| 1078W-G | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, Wide Gap, 1" Gap Size, Closed Loop, Gray |
| 1078W-M | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, Wide Gap, 1" Gap Size, Closed Loop, Brown |
| 1078W-N | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, Wide Gap, 1" Gap Size, Closed Loop, White |
| 1078WN-3.3K | Recessed Steel Door Contact w/Wire Leads, 1" Diameter, Wide Gap, 3.3K Ohm Resistor, 1" Gap Size, Closed Loop, White |
| R1078-M | Mini-Max Recessed Steel Door Contact w/Wire Leads, 1" Diameter, 1/2" Gap Size, Brown |
| R1078-N | Mini-Max Recessed Steel Door Contact w/Wire Leads, 1" Diameter, 1/2" Gap Size, White |

Specifications

Form A: (R)1078, 1078W, 1078C, 1078CT, 1078CTW


| | |
|---------|-----------------|
| Voltage | 100V AC/DC max. |
| Current | 0.5 A max. |
| Power | 7.5 W max. |

Form C: 1076, 1076W, 1076D, 1076C(D), 1076CW, 1076CH


| | |
|---------|----------------|
| Voltage | 30V AC/DC max. |
| Current | 0.25 A max. |
| Power | 3.0 W max. |

Dimensional Diagram


Models: (R)1078, 1078W, 1076, 1076W, 1076D




Models: 1078C, 1076C, 1076CW, 1076CH



Models: 1078CT, 1076CTW



Rare Earth Magnet



(R) prefix indicates
Rare Earth Magnet

Protected by
U.S. Patent 5,844,458.



interlogix.com

Specifications subject to change without notice.

© 2013 United Technologies Corporation.

All rights reserved.

Interlogix is part of UTC Climate, Controls & Security,
a unit of United Technologies Corporation.

306-3685 2013/11 (75103)