



DD 12040 - 12V 4Ah - C20



F1 Terminal

Features

- Special grid alloy and plate design
- Long service life, up to 5 years
- High charging performance
- High gas recombination technology
- Low-self discharge characteristic
- Wide operating temperature range

Application

- Measuring instrument
- Medical equipments
- Telephone sets
- Lighting equipment
- Security & alarm systems
- UPS power supply
- Power station and telecom station



ISO9001
ISO14000



CGZ3100705-02429-E


Specification

Cell per unit	6
Norminal Voltage	12V
Norminal Capacity	4 Ah
Weight	Approx. 1,30Kg (2,867lbs)
Internal Resistance	Approx. 50,4 mΩ
Norminal Operating Temperature Range	25°C
Recommended Maximum Charging Current Limit	1 A max
Float Charging Voltage	13,6 to 13,8VDC/unit Average at 25□ (77□)
Equalization and Cycle Service	14,1 to 14,4VDC/unit Average at 25□ (77□)
Self Discharge	Reddot Batteries can be stored for more than 6 months at (25°C/77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	F1


Characteristics

Rated Capacity	20 hour rate(0,2A)	4,0AH
	10 hour rate(0,4A)	3,8AH
	5 hour rate(0,64A)	3,2AH
	27 min rate(4A)	1,8AH
	7 min rate(12A)	1,4AH


Charging Characteristics(25°C/77°F)




The Relation between Discharging Current and Discharging time(25°C/77°F)



Discharging Characteristic(25°C/77°F)



Self-Discharging Characteristic(25°C/77°F)



Constant Current Discharge Characteristics (Amperes at 25°C)

Cut-off Voltage/cell	5min	10min	20min	45min	1Hr	2Hr	4Hr	8Hr	10Hr	20Hr
1,70	14,5	9,44	5,27	2,74	2,28	1,42	0,79	0,449	0,388	0,204
1,75	14,4	9,35	5,22	2,72	2,27	1,36	0,77	0,445	0,384	0,202
1,80	14,2	9,25	5,17	2,69	2,25	1,31	0,76	0,440	0,380	0,200

Constant Power Discharge Characteristics (Watts at 25°C)

Cut-off Voltage/cell	5min	10min	20min	45min	1Hr	2Hr	4Hr	8Hr	10Hr	20Hr
1,70	174	113	63,2	32,9	27,4	17,0	9,48	5,39	4,62	2,43
1,75	172	112	62,6	32,6	27,2	16,4	9,32	5,34	4,57	2,41
1,80	170	111	62,0	32,3	27,0	15,7	9,12	5,28	4,52	2,38

All mentioned values are average values