

DS-KIS702/S#Europe

- 2-wire digital IP video intercom kit for villa or house, only one call button
- DS-KD8003-IME2/Surface x1
- DS-KH6320-WTE2 x1
- DS-KAD704 x1
- DS-KAW30-2N x1
- 16GB TF card x1

www.hikvision.com

▪ Specification

Model			DS-KIS702/S#Europe
Door station	System parameters	Processor	Embedded microcontroller
		Operation system	Embedded Linux operation system
		Operation mode	One touch key
Door station	Video parameters	Camera	2MP super definition camera
		Resolution	Main stream: 1920 × 1080, (720p configurable); sub stream: 720 × 480
		Night vision	Support low light and IR light supplement mode
		Backlight compensation	Support
		Digital noise reduction	Support
		WDR	True WDR
		Field of view	Horizontal 180°, vertical 96°
		Video Compression Standard	H.264
		Stream	Main stream: 1080p@30fps, 720p@30fps (configurable); sub stream: D1
		Motion detection	Support
Door station	Audio parameters	Flash-avoid frequency	50 Hz, 60 Hz
		Audio input	Built-in omnidirectional microphone
		Audio output	Loudspeaker, 20 cm sound effect > 80 db
		Audio quality	Noise suppression and echo cancellation
		Audio compression standard	G.711 U
		Audio compression Rate	64 Kbps
Door station	Device inter	Audio intercom	Full-duplex two-way audio intercom
		RS-485	1 (inter-module connection)
		Alarm input	1

	faces		
Door station	General	Working temperature	-40 °C to 60 °C (-40 °F to 140 °F)
		Working humidity	10% to 90%
		Installation	Wall mounting
		Protection level	IP 65
		Button	1
		Power input	24 VDC two-wire power supply (< 16 W)
Indoor station	System parameters	Operation system	Embedded Linux operation system
		Processor basic frequency	1 GHz
		Memory	128 MB
		Flash	16 MB
Indoor station	Display parameters	Display screen	7-inch TFT LCD
		Display resolution	1024 × 600
		Operation method	Capacitive touch
Indoor station	Audio parameters	Audio input	Built-in omnidirectional microphone
		Audio output	Built-in loudspeaker
		Audio quality	Noise suppression and echo cancellation
		Volume	Local or software control
		Audio compression standard	G.711 U, G.711 A
		Audio compression Rate	64 Kbps
Indoor station	Network parameters	Wired network	Two-wire network
		Wireless network	Wi-Fi 802.11b/g/n
		Protocol	TCP/IP, SIP, RTSP
Indoor station	Device interfaces	Network interface	Two-wire interface
		RS-485	1
		Alarm input	8 zones alarm input
		Relay output	2
		TF card	Support, Max. 32 GB







Indoor station	General	Power supply	Two-wire
		Power consumption	≤ 6 W
		Working temperature	-10 °C to 50 °C (14 °F to 122 °F)
		Working humidity	10% to 90%
		Dimensions (W × H × D)	200 mm × 140 mm × 15.1 mm (7.87" × 5.51" × 0.59")
Video Audio Distributor	Interfaces	Network interface	1 RJ45
		Two-wire interface	4
		Signal indicator	4
		Power indicator	1
		Reset	1
Video Audio Distributor	General	Power supply	Two-wire mode
		Power consumption	CH1 to CH3<6 W, CH4<8 W
		Working temperature	-10 °C to +50 °C (14 °F to +122 °F)
		Working humidity	10% to 90%
		Digital noise reduction	Support

▪ Available Model

DS-KIS702/S(海外标配)/Europe BV,

▪ Accessory

▪ Optional

DS-KAW30-2N	DS-KH6320-WTE 2#EU&UK	DS-KAD704 Villa Two Wire Kit	DS-KH6320-WTE 2(B)	1 Rain Shield of Module Door Station
				
				
DS-KD8003-IME2 /S Two wire main unit	DS-KH6320-WTE 2 Two wire indoor stations	DS-KD8003-IME2 Two wire main unit		
				
				



Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com