

SLIM LINE MOTION DETECTOR COMPARISON CHART

	SLIM-PIR	SLIM-PIR- -PET	SLIM-PIR- -LUNA	SLIM-PIR- -LUNA-PET	SLIM-PIR- -PRO	SLIM-DUAL	SLIM-DUAL- -PET	SLIM-DUAL- -LUNA	SLIM-DUAL- -LUNA-PET	SLIM-DUAL- -PRO
Sensor	PIR	PIR	PIR	PIR	PIR	PIR+MW	PIR+MW	PIR+MW	PIR+MW	PIR+MW
Motion detection digital algorithm	•	•	•	•	•	•	•	•	•	•
Sensor self-test	•	•	•	•	•	•	•	•	•	•
Digital interference filter	•	•	•	•	•	•	•	•	•	•
Sensitivity adjustment	stepless	stepless	stepless	stepless	stepless	stepless	stepless	stepless	stepless	stepless
Digital temperature compensation	•	•	•	•	•	•	•	•	•	•
Remote LED disable	•	•	•	•	•	•	•	•	•	•
Active IR anti-masking					•					•
Anti-masking feature										
Cloaked intruder detection								•	•	•
Pyrosensor type	dual	quad	dual	quad	dual	dual	quad	dual	quad	dual
Optic type	Fresnel - replaceable	Fresnel	Fresnel - replaceable	Fresnel	Fresnel - replaceable	Fresnel - replaceable	Fresnel	Fresnel - replaceable	Fresnel	Fresnel - replaceable
Bracket	option		•		•	Option		•		•
Immunity to small pets movement		•		•			•		•	
Range	15 x 20 m, 90°	12 x 13 m, 90°	20 x 24 m, 90°	12 x 13 m, 90°	20 x 24 m, 90°	15 x 20 m, 90°	12 x 13 m, 90°	20 x 24 m, 90°	12 x 13 m, 90°	20 x 24 m, 90°
Built-in EOL resistors	•	•	•	•	•	•	•	•	•	•
Other unique features	selectable LED indicator color	selectable LED indicator color	lighting feature, selectable LED indicator color, configurable using OPT-1 keyfob, possibility to switch between two sensitivity levels	lighting feature, selectable LED indicator color, configurable using OPT-1 keyfob, possibility to switch between two sensitivity levels	selectable LED indicator color, configurable using OPT-1 keyfob	selectable LED indicator color (alarm signalisation)	selectable LED indicator color (alarm signalisation)	lighting feature, selectable LED indicator color, configurable using OPT-1 keyfob, possibility to switch between two sets of detector operating parameters	lighting feature, selectable LED indicator color, configurable using OPT-1 keyfob, possibility to switch between two sets of detector operating parameters	selectable LED indicator color configurable using OPT-1 keyfob