

DS-K1T502DBWX-E1 Pro Card Terminal



- Manage access control and intercom functions in one device
- IP65 & IK09 protections, as well as increased stability with zinc alloy materials
- Supports multiple authentication methods (card, PIN, QR code, etc.)
- Remote control via the Hik-Connect mobile app
- Connects to external access controller via Wiegand protocol
- Intercom via SIP protocol. Supported SIP server: Brekeke, miniSipServer, FreePBX, Asterisk, 3CX, ELASTIX, and PBXware
- RS-485 communication for connecting external card reader and calling elevator
- Supports AP mode
- Supports communication with smart phones via bluetooth to open the door
- Press calling button to call one of the following objects: management center, indoor station, specified indoor station, or Hik-Connect App
- Supports PIN settings under platform mode and local mode
- Setting the priority of wired network and wireless network is available
- Supports PoE power supply, and the device can directly supply power to the door lock, with a lock output power of 12V, 1A
- Supports dual relays, allowing control of two doors via Indoor Station, Web operation, etc.


▪ Specification

Network	
Wired network	Support
Wi-Fi	Support, 2.4 G, 802.11b/g/n
Interface	
Network interface	1 RJ-45 10/100 Mbps self-adaptive
Lock control	2
Exit button	1
Door contact input	1
Alarm input	2
Alarm output	1
TAMPER	1
RS-485	1,RS-485 (Half duplex,HIKVISION)
Wiegand	1 Wiegand(Hik 26bit,Hik 34bit)
SD card slot	1
Authentication	
Card type	M1 card,DESfirecard
General	
Built-in access controller	Support
Power supply	802.3at POE,12 VDC to 24 VDC, 1 A
Power consumption	≤ 24 W
Working temperature	-40 °C to 65 °C (-40 °F to 149 °F)
Language	Arabic, English, French, Indonesian, Italian, Portuguese (Brazil), Russian, Spanish (Europe), Thai, Ukrainian, Vietnamese, German, Polish, Hungarian, Czech, Romanian, Bulgarian, Croatian, Serbian, Greek, Slovak, Portuguese, Dutch, and Turkish
Function	
Hik-Connect	Support

▪ Available Model

DS-K1T502DBWX-E1(STD)

▪ Dimension



See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®