

DS-PR1-60 Security Radar

DS-PR1-60 security radar, which adopts phased array technology, pulse doppler and low-power FMCW modulation technology for intrusion detection. It supports multi-target positioning, tracing and multiple linked cameras tracking. Through intelligent algorithm analysis, it can filter out false alarms under various circumstances. It can work properly day and night in various environments, such as rain, fog, and so on. It is mainly used in the military base, prison, power station, railway, museum, airport and other security places.



Key Features

- Animal immunity: max. 20 kg
- Analysis with intelligent algorithm of anti-sway
- Links up to 4 speed domes for auto target-tracking and the speed domes can be mounted separately
- Capable to detect ultra-slow movements, squatting movements or creeping
- Displays the distance, direction, and position of the detected object on the client software
- Selectable applications including open mode, shrub mode, and custom mode (with adjustable sensitivity)
- 24/7 all-weather working properly
- Exception alarm: communication failure alarm, movement alarm, tampering alarm, anti-masking detection alarm
- Dual-color indicator displays radar status
- Supports standard PoE and 12 VDC
- Protection level: IP67



Specifications

Model		DS-PR1-60
Basic parameters	Modulation	Frequency Modulated Continuous Wave
	Detection range	60 m
	Horizontal angle	100°
	Range measurement accuracy	± 0.75 m
	Velocity measurement accuracy	± 0.1 m/s
	Angle measurement accuracy	± 1°
	Velocity range	- 8.7 to + 8.7 m/s
	Coverage	3000 m ² (32275.2 ft ²)
	Max. target number	32
	Frequency	24 GHz
	Consumption	6 W
	Transmission power	< 20 dBm (100mW)
Alarm input	Zone	8
Alarm output	Relay output NO/NC	3-channel : 0.5 A/125 VAC, breakdown voltage : 1 KV 1-channel : 10 A/240 VAC, breakdown voltage : 2.5 KV
Communication protocol	Network protocol	HTTP, DNS, NTP, TCP, UDP, DHCP, ARP, SSH
Interface	Network interface	1 RJ45 10M/100M self-adaptive, PoE
	Power interface	802.3at standard PoE or 12 VDC
	Reset button	1
General	Operation temperature	-40 °C to 65 °C (-40 °F to 149 °F)
	Operation humidity	10% to 90%
	Dimension (W × H × D)	206 mm × 228 mm × 61 mm (8.11" × 8.98" × 2.40")
	Consumption	< 10 W
	Protection level	IP67
	Weight	1.84 kg (4.06 lb)
	Color	White
Installation	Installation	Installation height:1.2 m to 4 m (4.72 " to 15.7 ") (Recommended: 2.5 m (9.84 "))

Available model

DS-PR1-60

Distributed by

**RIEL Elektronikai Kft.**

1139 Budapest, Rőppentyű u. 24.
 Tel.: +36 1 236 8090
 E-mail: info@riel.hu
www.riel.hu

HIKVISION®**Headquarters**

No.555 Qianmo Road, Binjiang District,
 Hangzhou 310051, China
 T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
 T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
 T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
 T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
 T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
 T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
 T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
 T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
 T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
 T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
 T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
 T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
 Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
 T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
 T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
 T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
 T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
 T +65-6684-4718
sg@hikvision.com

Hikvision Spain
 T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
 T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
 T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
 T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
 T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
 T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
 T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com