

# DSA-12PAG-12-3A-CCTV

36W Constant voltage desktop type AC/DC adapter



## ■ Features:

- Universal AC input / Full range
- Desktop type, Isolation class II design
  - IEC C320-C8 input AC socket
  - ErP step II / CEC level VI compliance
- No load power consumption  $P < 0.1W$
- Protections: Overload / Short circuit / Over Voltage

## ELECTRICAL SPECIFICATION



MODEL	ERD36W12V
-------	-----------

### OUTPUT

Rated Voltage	12V
Rated Current	3A
Current Range	0 ÷ 3A
Rated Power	36W
Line Regulation	± 1%
Load Regulation	± 2%
Tolerance [3]	± 8%
Ripple & Noise (max.) [2]	200mV <sub>p-p</sub>
Setup, Rise Time [4]	1030ms, 46ms / 230VAC at full load
Hold up Time (typ.)	60ms / 230VAC at full load

### INPUT

Voltage Range	90 ÷ 264VAC
Frequency Range	47 ÷ 63Hz
Efficiency (typ.)	84.6%
AC Current (typ.)	0.66A / 115VAC, 0.34A / 230VAC
No load Power Consumption (max.)	0.1W

### PROTECTIONS

Overload	Range: 105-200% Type: hiccup mode, auto-recovery.
Short Circuit	Type: hiccup mode, auto-recovery.
Over Voltage	16V Type: hiccup mode, auto-recovery.

# DSA-12PAG-12-3A-CCTV

36W Constant voltage desktop type AC/DC adapter

## WORKING ENVIRONMENT

<b>Working Temperature</b>	0°C ÷ 35°C
<b>Working Humidity</b>	5 ÷ 95% RH non-condensing
<b>Storage Temperature and Humidity</b>	-20°C ÷ 85°C, 5 ÷ 90% RH non-condensing

## SAFETY and EMC REGULATIONS

<b>Safety Standards</b>	Compliance to EN 60950-1
<b>Withstand Voltage</b>	IN/OUT: 3.6kVAC
<b>Isolation Resistance</b>	IN/OUT: 20MΩ/500VDC/25°C/70%
<b>EMC Emission</b>	Compliance to EN55032
<b>EMC Immunity</b>	Compliance to EN61000-4-2, -3, -4, -5
<b>Harmonic Current</b>	Compliance to EN61000-3-3; EN61000-3-2

## OTHERS

<b>AC Inlet</b>	IEC320-C8	
<b>DC wire and plug</b>	Wire: 18AWG*2C, length = 1500mm	Plug: 2.1/5.5, positive inside
<b>MTBF</b>	60 000h	
<b>Dimensions</b>	96.2 x 51.4 x 32.3mm (L x W x H)	
<b>Net Weight</b>	170.1g	

EAN Code



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1μF i 47μF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

## MECHANICAL SPECIFICATION

