

LINEAR HEAT DETECTOR CABLES - HDC

EN 54-28 FIRE DETECTION AND ALARM SYSTEM.
PART 28 NON-RESETTABLE LINE-TYPE HEAT DETECTORS.

- HDC - 68
- HDC - 88
- HDC - 105
- HDC - 138



UL-EU CERTIFICATE

Certificate No. UL-EU-01287-EN
Page 15
Date of Issue 2023-03-06

Certificate Holder Caviced S.p.A.
via Caduti del Lavoro 18A - 20096 - Pioselle, Italy

Manufacturer Same as Certificate Holder

Certified Product Type Non-resettable line-type heat detectors

Product Trade Name HDC-68 Heat Detector Cable
HDC-105 Heat Detector Cable

Trademark

Rating Classification See Appendix

Harmonised Technical Specifications EN54-28:2016

Supporting Documentation S35047-001-EuropeanDirective-Original

Additional information NA

Expiry date 2033-03-06

Authorized Certification Decision Maker Richard Dineen

www.ul.com



LINEAR HEAT DETECTOR CABLES - HDC

HDC LINEAR HEAT DETECTOR CABLES ARE RELIABLE AND ECONOMIC TOOLS FOR MONITORING ABNORMAL HEAT INCREASE WHICH OFTEN IS A PRELIMINARY STAGE OF A FULL FIRE EVENT.

The **HDC** sensor cable detects heat anywhere along its length: it is a **continuous** heat detector unlike the standard point detector. The **HDC** sensor cable is composed by two copper covered steel wires, individually insulated with a thermosensitive polymer. At the rated temperature the polymer insulation melts, thus permitting the conductors to short-circuit and generate an alarm signal. Four temperature alarm levels are available: **68 °C, 88 °C, 105 °C** and **138 °C**.

APPLICATIONS

Pipelines
Storage Tanks
Cable Trays
Aircraft Hangars
Control Rooms
Warehouses
Bridges and Tunnels
Mines
Cooling Towers
Escalators

APPROVAL AND CERTIFICATION

HDC cables (Heat Detector Cables) can also be supplied with certification issued by a Notified Body in compliance with the EN 54-28:2016 standard. All the tests prescribed by the standard as per the attached certification were carried out at the laboratory UL LLC – Northbrook – USA to guarantee compliance with all the requirements of the standard.

Cable Types: HDC-UL 68, HDC-UL 105

Certified Product Type: Non-resettable line-type heat detectors

Certificate No. ULEU-01267-EN

Date of Issue: 06-03-2023



	HDC-68	HDC-88	HDC-105	HDC-138
Alarm temperature	68±10%	88±10%	105±10%	138±10%
Outer sheath colour	red	white	black	blu
Conductors	Copper covered steel wire, ø 0.95 mm			
Insulation	Special thermosensitive polymer, red and black			
Cabling	Twisted insulated conductors			
Sheath	Extruded thermoplastic sheath			
Outer diameter	4.5 mm			
Weight	25 kg/km			
Max. ambient temperature	40°C 50°C 60°C 70°C			
Voltage rating	50 V a.c. or 120 V d.c.			
Conductor resistance	300 Ω/km @ 20 °C			
Dielectric test	500 V d.c. x 1'			
Water and oil sheath resistance	good			
Flame propagation	IEC 60332-1			
Fire reaction CPR	Eca - EN 13501-6			
RoHS II	2011/65/EU			
CE	2014/35/EU			

HEADQUARTERS AND FACTORY

Via Caduti del Lavoro, 18/A
20090 Pioltello (Milano)
Italy
Ph: +39 02 921 605 21
Fax: +39 02 921 607 53
e-mail: cavicel@cavicel.com

DUBAI OFFICE

Fortune Executive Tower
Office 406 - Plot n. T1
Jumeirah Lakes Towers
Dubai - UAE
Ph: +971 4 4581199
Fax: +971 4 4581144
e-mail: middleeast@cavicel.com

HONG KONG OFFICE

2/F, AXA Southside Building
38 Wong Chuk Hang Road
Hong Kong
Ph: +852 3963 9365
e-mail: apac@cavicel.com

www.cavicel.com


MADE IN ITALY