



Cat 6 S/FTP Patch Cable, 26 AWG, Pure Bare Copper

Model: NCN-P1C6SF-xxCLSBL

Main Features:

- ✦ Stranded Pure Bare Copper, 26 AWG;
- ✦ 1U gold-plated contacts for optimized signal integrity;
- ✦ 4 Twisted Pairs with filler reduce crosstalk, noise, and interference;
- ✦ HDPE Insulation enhances signal integrity and reduces signal loss;
- ✦ Fluke Tested for Reliable Performance.

Product Type

Category	Cat 6
Connector	2x RJ45 Male (8P8C, 1U Gold Plating)
Shielding	S/FTP

Conductor

Conductor Type	Stranded
Conductor Material	Pure Bare Copper
Conductor Size	7/0.16±0.008 mm
Wire Gauge	26 AWG
Conductor Quantity	4 Twisted Pairs
Wire Code	1. Blue / White-Blue 2. Orange / White-Orange 3. Green / White-Green 4. Brown / White-Brown

Insulation

Insulation Material	HDPE
Minimum Average Thickness	0.15 mm
Outer Diameter	0.95±0.08 mm

Filler

Material	HDPE
----------	------

Foil Shield

Material	Aluminum Mylar foil
----------	---------------------

Coverage	100%
----------	------

Overlap	25%
---------	-----

Drain

Material	Pure Bare Copper
----------	------------------

Size	7/0.12±0.008 mm
------	-----------------

Wire Gauge	28 AWG
------------	--------

Braid

Material	Aluminum Magnesium Wire
----------	-------------------------

Size	16*4/0.12±0.008 mm
------	--------------------

Jacket

Material	LSZH
----------	------

Minimum Average Thickness	0.51 mm
---------------------------	---------

Outer Diameter	6.0±0.2 mm
----------------	------------

Electrical Properties

Standard Bandwidth	250 MHz
--------------------	---------

Input Impedance	100±15% Ω (@4~100 MHz); 100±22% Ω (@100~250 MHz)
-----------------	--

Propagation Delay	≤ 548 ns/100m
-------------------	---------------

Propagation Skew	≤ 45 ns/100m
------------------	--------------

Unbalanced capacitance	≤ 330 pF/100m (Pair to Ground)
------------------------	--------------------------------

Conductor Resistance Unbalance	≤ 5%
--------------------------------	------

Insulation Resistance $\geq 5000 \text{ M}\Omega\cdot\text{km}$

Mechanical Properties

Min. Bending Radius $8\times \text{Cable OD}$

Environment

Operating Temperature -15°C to 70°C

Operating Humidity RH 10% to 90% (non-condensing)

Storage Temperature -40°C to 80°C

Storage Humidity RH 5% to 96% (non-condensing)

General

Color Blue

Length 0.25/0.5/1/2/5/10/20 meter

Diagram

