



IP67 Waterproof PoE Splitter for IP Camera

Model: NOS-11E-12D-W

Main Features:

- ✧ Plug-and-play installation with no configuration required;
- ✧ Support IEEE 802.3af PoE standards, 12 VDC, 1 A;
- ✧ IP67 waterproof design for outdoor use.

I/O Interfaces

Power Output	1x 5.5*2.1 mm DC plug (max. 12 VDC, 1A)
Ethernet Ports	1x 10/100 Mbps RJ45 PoE Input Port 1x 10/100 Mbps RJ45 Output Port

Standards

Network Standards	IEEE 802.3i (10BASE-T Ethernet)
	IEEE 802.3u (100BASE-TX Fast Ethernet)
	IEEE 802.3x (Flow Control)
PoE Standards	IEEE 802.3af
Network Media	10BASE-T: UTP category 3, 4, 5 cable (max. 100 m)
	100BASE-TX: UTP category 5 or above cable (max. 100 m)

Environment

Operating Temperature	-10°C to 50°C
Operating Humidity	RH 10% to 90% (non-condensing)
Storage Temperature	-40°C to 85°C
Storage Humidity	RH 5% to 95% (non-condensing)



nestron

General

Power Supply	max. 12 VDC, 1A
Shell Material	PC
Dimension	Ø23 x 100 mm (DxL) pigtail length 129 mm
Net Weight	45 g
Gross Weight	46 g
