

Cat 6 Shielded Keystone Coupler for Blank Patch Panel



Model: NPN-KEY-1C6SF-RJ45

Main Features:

- ✧ Mounted in Blank Patch Panel or Stand-alone Use;
- ✧ Connect two RJ45 patch cables to make a longer one;
- ✧ Durable design: ≥ 750 mating cycles;
- ✧ 3U Gold-plated contacts for enhanced conductivity.

Connector Type

Category	Cat 6
Connector	2x RJ45(8P8C) Female Ports
Shielding	Shielded

Material

Housing Material	Polycarbonate + Zinc Alloy
Contact Material	Phosphor Bronze with Nickel Plating, thickness = 0.3 mm
Contact Surface Material	Gold Plating, thickness = 3U (3 μ m or 0.0762 μ m)
PCB Material	FR-4, thickness = 1.6 mm

Electrical Properties

Voltage/Current Rating	125 VAC RMS / 1.5 A
Insulation Resistance	≥ 1000 M Ω at 500 VDC
Contact Resistance	≤ 100 m Ω
Dielectric Strength	750 VAC RMS, 60 Hz, 1 minute

Mechanical Properties

RJ45 Jack	≥ 750 mating cycles
Wire Gauge	AWG 22-26
Wiring Scheme	T568A/T568B

Environment

Operating Temperature	-25°C to 70°C
Operating Humidity	RH 10% to 90% (non-condensing)
Storage Temperature	-40°C to 85°C
Storage Humidity	RH 5% to 96% (non-condensing)

General

Dimension	14.5 x 19.6 x 29.6 mm (WxHxD)
Net Weight	17.8 g (dust cap included)

Diagram unit: mm

