



Cat 5e UTP Modular RJ45 Connector, 1U Gold-Plated Contacts

Model: NPN-RJ45-1C5U-PC10 / NPN-RJ45-1C5U-PC100

Main Features:

- ♦ Durable design: \geq 1000 mating cycles;
- ♦ Trident head ensures stable contact for rapid transmission;
- ↓ 1µin gold-plated contacts for optimized signal integrity.

Connector Type

Category	Cat 5e
Туре	8P8C (Eight Position, Eight Contact)
Shielding	Unshielded

Material

Housing Material	Polycarbonate
Contact Material	Copper
Contact Surface Material	Gold Plating on Nickel Barrier
Gold Plating Thickness	1U (1μin or 0.0254μm)

Electrical Properties

Voltage/Current Rating	125 VAC / 1.5 A
Insulation Resistance	≥ 500 MΩ
Contact Resistance	≤ 20 mΩ
Dielectric Withstand Voltage	1500 V DC/AC Peak

Mechanical Properties

Durability	≥ 1000 mating cycles
Wire Gauge	0.85 mm ≤ Ø ≤ 1.1 mm



Environment

Operating Temperature	-40°C to 70°C
Operating Humidity	RH 10% to 90% (non-condensing)
Storage Temperature	-40°C to 80°C
Storage Humidity	RH 5% to 96% (non-condensing)
General	
Dimension	23x12x8 mm (LxWxH)
Net Weight	1.5 g

Diagram

