

SLIM-R-PIR-LUNA BUS

SLIM-R-PIR-LUNA BUS is an indoor ceiling motion detector from the SLIM LINE series, designed for **recessed ceiling mounting**. The detector can be connected to the RS communication bus of a SATEL alarm control panel supporting bus-connected devices.

The device is also available in a version designed for surface-mounted ceiling installation (**SLIM-S-PIR-LUNA BUS**).

- compliant with the EN 50131 Grade 2 requirements
- motion detection using a passive infrared (PIR) sensor
- maximum detection area:
 - $\varnothing 6\text{ m} / 28\text{ m}^2$ – mounting height 2,4 m
 - $\varnothing 10\text{ m} / 79\text{ m}^2$ – mounting height 3,5 m
- adjustable detection sensitivity
- digital motion detection algorithm
- digital temperature compensation
- RS communication bus
- settings configuration via the RS bus
- firmware update via the RS bus
- built-in temperature sensor (measurement range: -10°C to $+55^{\circ}\text{C}$)
- lighting function implemented using LEDs
- remote lighting control
- LED indicator
- supervision of the motion detection circuit
- 12 V DC power supply ($\pm 15\%$)
- power supply monitoring
- tamper protection against enclosure opening
- installation in suspended ceilings



Supply voltage	12 V DC
Detected target velocity	0.3...3 m/s
Operating temperature range	$-10^{\circ}\text{C}...+55^{\circ}\text{C}$
Recommended mounting height	2,4...3,5 m
Standby mode current consumption	11 mA
Max. current consumption	65 mA
Weight	143 g
Maximum humidity	93 $\pm$ 3
Dimensions	$\varnothing 130 \times 42\text{ mm}$
Environmental class according to EN50130-5	II
Alarm signaling time	2 s
Complied with standards	EN 50131-1, EN 50131-2-2, EN 50130-4, EN 50130-5
Warm-up period	30 s
Security grade according to EN50131-2-2	Grade 2