

SLIM-S-DUAL-LUNA

SLIM-S-DUAL-LUNA is an indoor motion detector from the SLIM LINE series, designed for **surface-mounted ceiling installation**. It is an ideal solution for locations where wall-mounted detectors are impossible or undesirable. With its 360° detection coverage, it is well suited for monitoring shops, warehouses, and other areas where a ceiling-mounted detector facing downward provides more effective coverage than a wall-mounted detector.

This model is also available for recessed-mounting (**SLIM-R-DUAL-LUNA**).

- compliant with the **EN 50131 Grade 2** requirements
- lighting function:
 - remote lighting control
 - lighting activation by motion
- motion detection using two sensors: passive infrared (PIR) and microwave (MW)
- remote switching between two programmed sensitivity levels (SENS terminal)
- maximum detection area:
 - $\varnothing 6\text{ m} / 28\text{ m}^2$ – mounting height 2,4 m
 - $\varnothing 10\text{ m} / 79\text{ m}^2$ – mounting height 3,5 m
- digital motion detection algorithm for both sensors
- digital temperature compensation
- adjustable detection sensitivity for both sensors
- separate sensor testing feature
- digital filtering of signals received by the microwave sensor, ensuring immunity to interference caused by the power grid and discharge lamps
- selectable operating modes: basic, advanced, PIR, or MW
- detector operating parameter configuration:
 - on-board buttons
 - **OPT-1** remote keyfob
- built-in EOL resistors: 1,1 k Ω , 4,7 k Ω , 5,6 k Ω
- LED indicator:
 - selectable color (7 colors available)
 - remote on/off control
- remote enable/disable of configuration mode
- supervision of the motion detection circuit
- 12 V DC power supply (15%)
- power supply monitoring
- tamper protection against enclosure opening and removal from the mounting surface
- ceiling surface mounting



Alarm signaling time	2 s
EOL resistors	2 x 1,1 / 2 x 4,7 / 2 x 5,6 kΩ
Relay contact resistance (tamper output)	26 Ω
Relay contact resistance (alarm output)	26 Ω
Tamper outputs (NC relay, resistive load)	40 mA / 24 V DC
Alarm outputs (NC relay, resistive load)	40 mA / 24 V DC
Warm-up period	30 s
Security grade according to EN50131-2-4	Grade 2
Microwave frequency	24,125 GHz
Complied with standards	EN 50131-1, EN 50131-2-4, EN 50130-4, EN 50130-5
Supply voltage	12 V DC
Environmental class according to EN50130-5	II
Dimensions	ø 120 x 37 mm
Maximum humidity	93±3%
Weight	117 g
Max. current consumption	70 mA
Standby mode current consumption	12 mA
Recommended mounting height	2,4...3,5 m
Operating temperature range	-10 °C...+55 °C
Detected target velocity	0,3...3 m/s